

PRODUCT SPECIFICATION

S-MARK Dura-T

FLOOR MARKING TAPE HD

SKU: FM-3210



PRODUCT DESCRIPTION:

Self-Adhesive Heavy Duty Floor Marking Tape. Dura-T has a permanent adhesive, but can be removed cleanly due to its high tensile strength. The purpose of the tape is to create a visual aid for process and traffic management, safety and hygiene in warehouses, work, commercial and public spaces. The tape is suited to areas with foot traffic, trolleys, pallet and fork-trucks.

PHYSICAL PROPERTIES

Technical Descriptions	Value	Detail	Test Method
Backing material	PVC	0.55mm	Calliper
Protection film	PVC	0.15mm	Calliper
Adhesive	Solvent acrylic	0.24mm	Calliper
Max material width	-	1260mm	N/A

TECHNICAL PROPERTIES

Technical Descriptions	Value	Unit	Test Method
Adhesion to Steel	25.2	Kg/25.4mm	PSTC-1
Tack loop	28.0	Kg/25.4mm	PSTC-16
Cohesion at 25°C	158.0	Hrs	ASTM-7
Temperature range	-30 to +70	°C	-
Fire classification	Pass	-	ES13501/DIN11925

SLIP RESISTANCE

Pendulum Test	PTV Value	Class	Test Method
Dry surface	102	R10	DIN51130
Wet surface	24	R10	DIN51130

COLOURS

R=Red, O=Orange, Y=Yellow, G=Green, W=White, N=Black, D=Black&Yellow, A=Red&White

APPLICATION RECOMMENDATIONS

Use on sealed / non-porous surfaces only. Prior to application the surface should be dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure maximum adhesive contact.

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.